

Earthquake Topics for Education

[FAQ](#)[Earthquake Glossary](#)[For Kids](#)[Prepare](#)[Google Earth/KML Files](#)[Earthquake Summary Posters](#)[Photos](#)[Publications](#)

The Modified Mercalli Intensity Scale

The effect of an earthquake on the Earth's surface is called the intensity. The intensity scale consists of a series of certain key responses such as people awakening, movement of furniture, damage to chimneys, and finally - total destruction. Although numerous *intensity scales* have been developed over the last several hundred years to evaluate the effects of earthquakes, the one currently used in the United States is the Modified Mercalli (MM) Intensity Scale. It was developed in 1931 by the American seismologists Harry Wood and Frank Neumann. This scale, composed of increasing levels of intensity that range from imperceptible shaking to catastrophic destruction, is designated by Roman numerals. It does not have a mathematical basis; instead it is an arbitrary ranking based on observed effects.

The Modified Mercalli Intensity value assigned to a specific site after an earthquake has a more meaningful measure of severity to the nonscientist than the magnitude because intensity refers to the effects actually experienced at that place.

The **lower** numbers of the intensity scale generally deal with the manner in which the earthquake is felt by people. The **higher** numbers of the scale are based on observed structural damage. Structural engineers usually contribute information for assigning intensity values of VIII or above.

The following is an abbreviated description of the levels of Modified Mercalli intensity.

Intensity	Shaking	Description/Damage
I	Not felt	Not felt except by a very few under especially favorable conditions.
II	Weak	Felt only by a few persons at rest, especially on upper floors of buildings.
III	Weak	Felt quite noticeably by persons indoors, especially on upper floors of buildings. Many people do not recognize it as an earthquake. Standing motor cars may rock slightly. Vibrations similar to the passing of a truck. Duration estimated.
IV	Light	Felt indoors by many, outdoors by few during the day. At night, some awakened. Dishes, windows, doors disturbed; walls make cracking sound. Sensation like heavy truck striking building. Standing motor cars rocked noticeably.
V	Moderate	Felt by nearly everyone; many awakened. Some dishes, windows broken. Unstable objects overturned. Pendulum clocks may stop.
VI	Strong	Felt by all, many frightened. Some heavy furniture moved; a few instances of fallen plaster. Damage slight.
VII	Very strong	Damage negligible in buildings of good design and construction; slight to moderate in well-built ordinary structures; considerable damage in poorly built or badly designed structures; some chimneys broken.
VIII	Severe	Damage slight in specially designed structures; considerable damage in ordinary substantial buildings with partial collapse. Damage great in poorly built structures. Fall of chimneys, factory stacks, columns, monuments, walls. Heavy furniture overturned.
IX	Violent	Damage considerable in specially designed structures; well-designed frame structures thrown out of plumb. Damage great in substantial buildings, with partial collapse. Buildings shifted off foundations.
X	Extreme	Some well-built wooden structures destroyed; most masonry and frame structures destroyed with foundations. Rails bent.

Abridged from [The Severity of an Earthquake](#), a U. S. Geological Survey General Interest Publication. U.S. GOVERNMENT PRINTING OFFICE: 1989-288-913

This publication is one of a series of [general interest publications](#) prepared by the U.S. Geological Survey to provide information about the earth sciences, natural resources, and the environment.

Share this page: [Facebook](#) [Twitter](#) [Google](#) [Email](#)

EARTHQUAKES	HAZARDS	DATA & PRODUCTS	LEARN	MONITORING	RESEARCH
Latest Earthquakes	Hazard Maps & Data	Data	EQ Topics for Education	NEIC	Characterizing Faults
Real-time Feeds & Notifications	Seismic Design	Products	FAQ	ANSS – United States	Early Warning
Search EQ Archives	Hazard Analysis Tools		EQ Glossary	GSN – World	Crustal Deformation
Info by Region	Faults		For Kids	Volunteer Monitoring	Earthquake Processes
US Seismicity Map			Google Earth/KML Files	ASL – Albuquerque	Ground Failure
World Seismicity Maps			EQ Summary Posters	Network Operations	Ground Motion
"Top 10" Lists & Maps			Photos	Seismogram Displays	Hazard & Risk Assessment
Did You Feel It?			Publications	Buildings	Improving Monitoring
ShakeMap				NSMP – Strong Motion	Induced Earthquakes
PAGER				Crustal Deformation	External Support
Significant EQ Archive					Regional Science Activities
					Software

[Accessibility](#) [FOIA](#) [Privacy](#) [Policies and Notices](#) In partnership with [nehrp](#)

[U.S. Department of the Interior](#) | [U.S. Geological Survey](#)
 Page URL: <http://earthquake.usgs.gov/learn/topics/mercalli.php>
 Page Contact Information: [Contact Us](#)
 Page Last Modified: October 02, 2014 15:27:37 UTC



[DOJ](#) and [USGS](#) link policies apply.